

Mobile paint-spray extraction unit MiniMax F 300



Schuko

Dust extraction and filter technology

Mobile paint-spray extraction unit MiniMax Type F 300

The energy-saving and inexpensive paint-spray aspiration unit from Schuko offers you the advantages of a stationary system, without being bound to a particular location.

The two level filtration process ensured a high separation efficiency (includes fine dust filter mat Kat F5 following EN 779). The stable, self-supporting structure is secured against tilting on top of the solid chassis.

There is no reason to waive a paint-spray aspiration unit for occasional painting works, pickling or evaporating due to cost or space reasons.

Your health will thank you for it.

MiniMax	Type F 300
Item No.	517600
Air capacity	5,200 m ³ /h, 900 PA
Dimensions L x B x H	1,250 x 820 x 1,460 mm
Motor power	1.5 KW, 400 V, 50 Hz
Weight	140 kg
Air baffles	optional
Equipment incl.	
<ul style="list-style-type: none"> • Supply line 7 m • Motor protection plug (to be placed outside of the ATEX zone) 	
<p>Regarding placement and exhaust air conduction please consult BGI 740 of the Berufsgenossenschaft Holz und Metall (professional association for wood and metal) (BGHM, as per 06/2008)</p>	

The compact and reasonable prices paint-spray extraction system

Saving energy
benefits the
environment
and your wallet.



air baffles are optional

www.schuko.com